

**JP Patent Abstract, v 1. 1997, no. 3, JP 08287901
1327.003WO1**

3/9/1

DIALOG(R)File 351:Derwent WPI

(c) 2002 Thomson Derwent. All rts. reserv.

011048817 **Image available** WPI Acc No: 1997-026741/199703

XRAM Acc No: C97-008193 XRPX Acc No: N97-022519

**Positive pole for lithium sec. cell for power source of small and light wt. el
comprising material contg. at least lithium is vapour deposited on electrode
oxide film contg. lithium-oxide formed on substrate**

Patent Assignee: NISSHIN ELECTRICAL CO LTD (NDEN)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week

JP 8287901 A 19961101 JP 9593860 A 19950419 199703 B

Priority Applications (No Type Date): JP 9593860 A 19950419

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

JP 8287901 A 6 H01M-004/04

Abstract (Basic): JP 8287901 A

Method comprises: (a) a material contg. at least Li is vapour deposited on an electrode substrate and simultaneously ions are irradiated on the substrate; and (b) an oxide film contg. at least Li-oxide is formed on the substrate by blowing O₂ on the substrate.

USE - The cell is suitable for power source of smaller size and light wt. electronic appts..

ADVANTAGE - The electrode has improved property since adhesiveness of the oxide film with the electrode substrate is improved.

Dwg. 1/1

Title Terms: POSITIVE; POLE; LITHIUM; SEC; CELL; POWER; SOURCE; LIGHT; WEIGHT; ELECTRONIC; APPARATUS; COMPRISE; MATERIAL; CONTAIN; LITHIUM; VAPOUR; DEPOSIT; ELECTRODE; SUBSTRATE; OXIDE; FILM; CONTAIN; LITHIUM; OXIDE; FORMING; SUBSTRATE

Derwent Class: L03; X16

International Patent Class (Main): H01M-004/04

International Patent Class (Additional): C23C-014/22

File Segment: CPI; EPI

Manual Codes (CPI/A-N): L03-E01B5

Manual Codes (EPI/S-X): X16-E08A